Foam sprayer incl. jet spray, 1/2"(Q), 1.4 Litre, Blue





Clean sanitary and small processing areas, applying foam at normal water pressure. Ensures consistently correct dosage (0.4–10%). Colour-coding facilitates chemical identification. Safeone (9340) is recommended for protection against chemical reflux in potable water supplies and is approved according to EN 1717 - substance class 3.

Technical Data

outent ontent ontent aterial eets the REACH Regulation (EC) No. 1907/2006 CIP number se of phthalates and bisphenol A ox Quantity uantity per Pallet (80 x 120 x 200 cm) uantity Per Layer (Pallet) ox Length ox Width ox Height ength //idth eight et Weight	1/2 " 1,4 Litre 47,34 Fl oz Brass Orgalloy TSGZ 15
ontent aterial eets the REACH Regulation (EC) No. 1907/2006 CIP number se of phthalates and bisphenol A ox Quantity uantity per Pallet (80 x 120 x 200 cm) uantity Per Layer (Pallet) ox Length ox Width ox Height ength	47,34 Fl oz Brass Orgalloy
aterial eets the REACH Regulation (EC) No. 1907/2006 CIP number se of phthalates and bisphenol A ox Quantity uantity per Pallet (80 x 120 x 200 cm) uantity Per Layer (Pallet) ox Length ox Width ox Height ength //dth eight	Brass Orgalloy
eets the REACH Regulation (EC) No. 1907/2006 CIP number se of phthalates and bisphenol A ox Quantity uantity per Pallet (80 x 120 x 200 cm) uantity Per Layer (Pallet) ox Length ox Width ox Height ength //dth eight	Orgalloy
CIP number se of phthalates and bisphenol A ox Quantity uantity per Pallet (80 x 120 x 200 cm) uantity Per Layer (Pallet) ox Length ox Width ox Height ength //idth eight	
se of phthalates and bisphenol A ox Quantity uantity per Pallet (80 x 120 x 200 cm) uantity Per Layer (Pallet) ox Length ox Width ox Height ength //idth eight	Yes **
ox Quantity uantity per Pallet (80 x 120 x 200 cm) uantity Per Layer (Pallet) ox Length ox Width ox Height ength /idth eight	
uantity per Pallet (80 x 120 x 200 cm) uantity Per Layer (Pallet) ox Length ox Width ox Height ength /idth eight	No
uantity Per Layer (Pallet) ox Length ox Width ox Height ength //idth	1 Pcs.
ox Length ox Width ox Height ength //idth eight	160 Pcs
ox Width ox Height ength /idth eight	1 Pcs.
ox Height ength /idth eight	290 mm
ength /idth eight	190 mm
/idth eight	175 mm
eight	290 mm
	190 mm
et Weight	175 mm
	0,72 kg
/eight cardboard	0,162 kg
are total	0,162 kg
ross Weight	0,88 kg
ubik metre	0,009642 M3
ax. cleaning temperature (Dishwasher)	40 °C
ax usage temperature (non food contact)	40 °C
in. usage temperature³	5 °C
in. pH-value in usage concentration	2 pH
ax. pH-value in Usage Concentration	11 pH
in. Bars pressure	2 Bar
ax. bars pressure	6 Bar
tin-13 Number	5705020930539
TIN-14 Number (Box quantity)	5705020930536
ustoms Tariff No.	84818099
ountry of origin	

When the foam application is finalized, it is important to rinse the injector with clean water to avoid blocking of the nozzle. Screw the injector of the container and let it suck clean water through the suction hose to

enable hose, filter and nozzle to be rinsed for chemicals.

2/1/2021 3/3

^{**} Lead (Pb, CAS: 7439-92-1) is on the REACH candidate list as a Substance of Very High Concern (SVHC). This product contains lead (Pb) in a concentration above 0.1% w/w. Consequently the REACH Regulation (EC) No. 1907/2006 require Vikan to notify our customers of the content of lead. This product is registered in the EU SCIP database. Please find SCIP number above.